

GTRK



2021

PRODUCT SPEC

目 录
CONTENTS

E-BIKE/DH

850E-DH E-Bike ready ----- 01
850E E-Bike ready ----- 02
830E-DH E-Bike ready ----- 03
830E E-Bike ready ----- 04
810E-DH ready ----- 05
810E ready ----- 06

XC/ATB

740-110 series ----- 07
730-100 series ----- 08
680TA Boost series ----- 09
680TA series ----- 10
680 series ----- 11
550TA-110 series ----- 12
550TA series ----- 13
550 series ----- 14
366 series ----- 15
360A series ----- 16
368TA series ----- 17
368 series ----- 18
360 series ----- 19
330 series ----- 20

FAT BIKE

860DH series ----- 21
860 serie ----- 22
355DH series ----- 23
355 series ----- 24

CROSS TREKKING

328 series ----- 25
320 series ----- 26

KID BIKE

210 series ----- 27
212 series ----- 28

SCOOTER

107 series ----- 29
130 series ----- 30

SEAT POST

SP--01 ----- 31
SP--02 ----- 31

850E-DH E-Bike ready



- WHEEL SIZE: 27.5" 29"
STEERER SIZE: 28.6mm Carbon optional 1.5"
PITCH: 145mm
CROWN: Carbon coating black
STANCHION: 35mm AL7075 alumium hard anodize black
LOWER LEGS: Carbon 15mm QR/110mm
FEATURES: Hydraulic lock out with rebound adjustable
Air suspension
TRAVEL(mm): 140/160/180/200
BRAKE: Disc Only
WEIGHT: 1.67KG

850E E-Bike ready

AIR

HL/R



WHEEL SIZE: 27.5" 29"
STEERER SIZE: 28.6mm Carbon optional 1.5"
PITCH: 145mm
CROWN: Carbon coating black
STANCHION: 35mm AL7075 alumium hard anodize black
LOWER LEGS: Carbon 15mm QR/110mm
FEATURES: Hydraulic lock out with rebound adjustable
 Air suspension
TRAVEL(mm): 120/140/160
BRAKE: Disc Only
WEIGHT: 1.67KG

830E-DH E-Bike ready

NEW

AIR

HL/R



WHEEL SIZE: 27.5" 29"
STEERER SIZE: 28.6mm AL7075 alumium(Optional 1.5" aluminum tapered steerer)
PITCH: 145mm
CROWN: Aluminum coating black
STANCHION: 35mm AL7075 alumium hard anodize black
LOWER LEGS: Magnesium 15mm QR/110mm
FEATURES: Hydraulic lock out with rebound adjustable
 Air suspension
TRAVEL(mm): 140/160/180/200
BRAKE: Disc Only
WEIGHT: 2.81KG

830E E-Bike ready

810E-DH ready



NEW

AIR

HL/R



WHEEL SIZE: 27.5" 29"
STEERER SIZE: 28.6mm AL7075 alumium(Optional 1.5" aluminum tapered steerer)
PITCH: 145mm
CROWN: Aluminum coating black
STANCHION: 35mm AL7075 alumium hard anodize black
LOWER LEGS: Magnesium 15mm QR/110mm
FEATURES: Hydraulic lock out with rebound adjustable
 Air suspension
TRAVEL(mm): 120/140/160
BRAKE: Disc Only
WEIGHT: 2.355KG



NEW

AIR

HL/R

WHEEL SIZE: 20" 24" 26"
STEERER SIZE: 28.6mm AL7075 alumium(Optional 1.5" aluminum tapered steerer)
PITCH: 145mm
CROWN: Aluminum coating black
STANCHION: 34mm AL7075 alumium hard anodize black
LOWER LEGS: Aluminum 15mm QR/110mm
FEATURES: Hydraulic lock out with rebound adjustable
 Air suspension
TRAVEL(mm): 140/160/180/200
BRAKE: Disc Only
WEIGHT: 3.475KG



810E ready



NEW

AIR

HL/R



WHEEL SIZE: 20" 24" 26"
STEERER SIZE: 28.6mm AL7075 alumium(Optional 1.5" aluminum tapered steerer)
PITCH: 145mm
CROWN: Aluminum coating black
STANCHION: 34mm AL7075 alumium hard anodize black
LOWER LEGS: Aluminum 15mm QR/110mm
FEATURES: Hydraulic lock out with rebound adjustable
 Air suspension
TRAVEL(mm): 120/140/160
BRAKE: Disc Only
WEIGHT: 2.8KG

740-110 series



NEW

AIR

HL/R

WHEEL SIZE: 29"
STEERER SIZE: 28.6mm Carbon Optional 1.5"
PITCH: 142mm
CROWN: Carbon coating black
STANCHION: 32mm AL7075 alumium hard anodize black
LOWER LEGS: Carbon 15mm QR/110mm
FEATURES: Hydraulic lock out with rebound adjustable
 Remote lock out with rebound adjustable
 Air suspension
TRAVEL(mm): 80/100
BRAKE: Disc Only
WEIGHT: 1.71KG



730-100 series



WHEEL SIZE: 27.5" 29"
STEERER SIZE: 28.6mm Carbon Optional 1.5"
PITCH: 125mm
CROWN: Carbon coating black
STANCHION: 30mm AL7075 alumium hard anodize black
LOWER LEGS: Carbon 15mm QR/100mm
FEATURES: Hydraulic lock out with rebound adjustable
 Remote lock out with rebound adjustable
 Air suspension
TRAVEL(mm): 80/100
BRAKE: Disc Only
WEIGHT: 1.48KG

680TA Boost series



WHEEL SIZE: 27.5" 29"
STEERER SIZE: 28.6mm AL7075 alumium(Optional 1.5" aluminum tapered steerer)
PITCH: 130mm
CROWN: Aluminum coating black
STANCHION: 32mm AL7075 alumium hard anodize black
LOWER LEGS: Magnesium 15mm QR/110mm
FEATURES: Hydraulic lock out with rebound adjustable
 Remote lock out with rebound adjustable
 Air suspension
TRAVEL(mm): 100/120
BRAKE: Disc Only
WEIGHT: 1.68KG

680TA series



AIR

HL

RL

HL/R

RL/R



WHEEL SIZE: 27.5" 29"
STEERER SIZE: 28.6mm AL7075 alumium(Optional 1.5" aluminum tapered steerer)
PITCH: 130mm
CROWN: Aluminum coating black
STANCHION: 32mm AL7075 alumium hard anodize black
LOWER LEGS: Magnesium 15mm QR/100mm
FEATURES: Hydraulic lock out with rebound adjustable
 Remote lock out with rebound adjustable
 Air suspension
TRAVEL(mm): 100/120
BRAKE: Disc Only
WEIGHT: 1.68KG

680 series



AIR

HL

RL

HL/R

RL/R

WHEEL SIZE: 27.5" 29"
STEERER SIZE: 28.6mm AL7075 alumium(Optional 1.5" aluminum tapered steerer)
PITCH: 130mm
CROWN: Aluminum coating black
STANCHION: 32mm AL7075 alumium hard anodize black
LOWER LEGS: Magnesium 9mm open drop out/100mm
FEATURES: Hydraulic lock out with rebound adjustable
 Remote lock out with rebound adjustable
 Air suspension
TRAVEL(mm): 100/120
BRAKE: Disc Only
WEIGHT: 1.58KG



550TA-110 series



AIR

HL

RL

HL/R

RL/R



- WHEEL SIZE:** 27.5" 29"
- STEERER SIZE:** 28.6mm AL7075 alumium(Optional 1.5" aluminum tapered steerer)
- PITCH:** 132mm
- CROWN:** Aluminum coating black
- STANCHION:** 34mm AL7075 alumium hard anodize black
- LOWER LEGS:** Magnesium 15mm QR/110mm
- FEATURES:** Hydraulic lock out with rebound adjustable
Remote lock out with rebound adjustable
Air suspension
- TRAVEL(mm):** 100/120/140
- BRAKE:** Disc Only
- WEIGHT:** 2.08KG

550TA series



AIR

HL

RL

HL/R

RL/R

- WHEEL SIZE:** 27.5" 29"
- STEERER SIZE:** 28.6mm AL7075 alumium(Optional 1.5" aluminum tapered steerer)
- PITCH:** 132mm
- CROWN:** Aluminum coating black
- STANCHION:** 34mm AL7075 alumium hard anodize black
- LOWER LEGS:** Magnesium 15mm QR/100mm
- FEATURES:** Hydraulic lock out with rebound adjustable
Remote lock out with rebound adjustable
Air suspension
- TRAVEL(mm):** 100/120/140
- BRAKE:** Disc Only
- WEIGHT:** 2.08KG



550 series



NEW

AIR

HL

RL

HL/R

RL/R



- WHEEL SIZE:** 27.5" 29"
- STEERER SIZE:** 28.6mm AL7075 alumium(Optional 1.5" aluminum tapered steerer)
- PITCH:** 132mm
- CROWN:** Aluminum coating black
- STANCHION:** 34mm AL7075 alumium hard anodize black
- LOWER LEGS:** Magnesium 9mm open drop out/100mm
- FEATURES:** Hydraulic lock out with rebound adjustable
Remote lock out with rebound adjustable
Air suspension
- TRAVEL(mm):** 100/120/140
- BRAKE:** Disc Only
- WEIGHT:** 2.06KG

366 series



AIR

HL

RL

- WHEEL SIZE:** 26" 27.5" 29"
- STEERER SIZE:** 28.6mm AL7075 alumium(Optional 1.5" aluminum tapered steerer)
- PITCH:** 130mm
- CROWN:** Aluminum coating black
- STANCHION:** 32mm AL7075 alumium hard anodize black
- LOWER LEGS:** Magnesium 9mm open drop out/100mm
- FEATURES:** Hydraulic lock out with rebound adjustable
Remote lock out with rebound adjustable
Air suspension
- TRAVEL(mm):** 100/120
- BRAKE:** Disc Only
- WEIGHT:** 1.94KG



360A series



WHEEL SIZE: 26" 27.5" 29"
STEERER SIZE: 28.6mm AL7075 alumium(Optional 1.5" aluminum tapered steerer)
PITCH: 130mm
CROWN: Aluminum coating black
STANCHION: 32mm AL7075 alumium hard anodize black
LOWER LEGS: Aluminum 9mm open drop out/100mm
FEATURES: Hydraulic lock out
 Remote lock out
 Spring
TRAVEL(mm): 100/120
BRAKE: Disc Only
WEIGHT: 2.23KG

368TA series



WHEEL SIZE: 27.5" 29"
STEERER SIZE: 28.6mm Steel
PITCH: 132mm
CROWN: Aluminum coating black
STANCHION: 34mm steel CP/ED black
LOWER LEGS: Magnesium 15mm QR/100mm
FEATURES: Hydraulic lock out
 Remote lock out
 Mechanical lock out
 Adjustable
TRAVEL(mm): 100/120/140
BRAKE: Disc Only
WEIGHT: 2.88KG



368 series



NEW

AMS

ML

HL

RL



WHEEL SIZE: 27.5" 29"
STEERER SIZE: 28.6mm Steel
PITCH: 132mm
CROWN: Aluminum coating black
STANCHION: 34mm steel CP/ED black
LOWER LEGS: Magnesium 9mm open drop out/100mm
FEATURES: Hydraulic lock out
 Remote lock out
 Mechanical lock out
 Adjustable
TRAVEL(mm): 100/120/140
BRAKE: Disc Only
WEIGHT: 2.86KG

360 series



AMS

ML

HL

RL

WHEEL SIZE: 26" 27.5" 29"
STEERER SIZE: 28.6mm Steel
PITCH: 130mm
CROWN: Aluminum coating black
STANCHION: 32mm steel CP/ED black
LOWER LEGS: Aluminum 9mm open drop out/100mm
FEATURES: Hydraulic lock out
 Remote lock out
 Mechanical lock out
 Spring
TRAVEL(mm): 100/120
BRAKE: Disc Only
WEIGHT: 2.8KG





330 series



WHEEL SIZE: 24" 26" 27.5" 29"
STEERER SIZE: 28.6mm Steel
PITCH: 125mm
CROWN: Aluminum coating black
STANCHION: 28.6mm steel CP/ED black
LOWER LEGS: Aluminum 9mm open drop out/100mm
FEATURES: Hydraulic lock out
 Remote lock out
 Mechanical lock out
 Spring
TRAVEL(mm): 100/120
BRAKE: Disc Only
WEIGHT: 2.435KG

860DH series



WHEEL SIZE: 20" 24" 26"
STEERER SIZE: 28.6mm AL7075 alumium(Optional 1.5" aluminum tapered steerer)
PITCH: 185mm
CROWN: Aluminum coating black
STANCHION: 34mm AL7075 alumium hard anodize black
LOWER LEGS: Aluminum 15mm QR/150mm
FEATURES: Hydraulic lock out with rebound adjustable
 Air suspension
TRAVEL(mm): 160/180/200
BRAKE: Disc Only
WEIGHT: 3.865KG



860 serie



WHEEL SIZE: 20" 24" 26"
STEERER SIZE: 28.6mm AL7075 alumium(Optional 1.5" aluminum tapered steerer)
PITCH: 185mm
CROWN: Aluminum coating black
STANCHION: 34mm AL7075 alumium hard anodize black
LOWER LEGS: Aluminum 15mm QR/150mm
FEATURES: Hydraulic lock out with rebound adjustable
Air suspension
TRAVEL(mm): 160
BRAKE: Disc Only
WEIGHT: 2.935KG

355DH series



WHEEL SIZE: 20" 24" 26"
STEERER SIZE: 28.6mm AL7075 alumium(Optional 1.5" aluminum tapered steerer)
28.6mm Steel
PITCH: 171mm
CROWN: Aluminum coating black
STANCHION: 32mm AL7075 alumium hard anodize black
32mm steel CP/ED black
LOWER LEGS: Aluminum 9mm open drop out/135mm
FEATURES: Hydraulic lock out with rebound adjustable
Hydraulic lock out
Spring
TRAVEL(mm): 100/120
BRAKE: Disc Only
WEIGHT: 2.64KG

355 series



- WHEEL SIZE:** 20" 24" 26"
- STEERER SIZE:** 28.6mm AL7075 alumium(Optional 1.5" aluminum tapered steerer)
28.6mm Steel
- PITCH:** 171mm
- CROWN:** Aluminum coating black
- STANCHION:** 32mm AL7075 alumium hard anodize black
32mm steel CP/ED black
- LOWER LEGS:** Aluminum 9mm open drop out/135mm
Aluminum 15mm QR/135mm(20")
- FEATURES:** Hydraulic lock out with rebound adjustable
Hydraulic lock
Remote lock out
Mechanical lock out
Spring
- TRAVEL(mm):** 100/120
- BRAKE:** Disc Only
- WEIGHT:** 2.19KG

328 series



- WHEEL SIZE:** 27.5" 700C
- STEERER SIZE:** 28.6mm AL7075 alumium(Optional 1.5" aluminum tapered steerer)
28.6mm Steel
- PITCH:** 130mm
- CROWN:** Aluminum coating black
- STANCHION:** 32mm AL7075 alumium hard anodize black
32mm steel CP/ED black
- LOWER LEGS:** Magnesium 9mm open drop out/100mm
- FEATURES:** Hydraulic lock out with rebound adjustable
Remote lock out with rebound adjustable
Air suspension
Hydraulic lock
Remote lock out
Mechanical lock out
Spring
- TRAVEL(mm):** 60/80/100
- BRAKE:** Disc Only
- WEIGHT:** 1.67KG(AIR)



320 series



WHEEL SIZE: 700C
STEERER SIZE: 28.6mm Steel
PITCH: 107mm
CROWN: Aluminum coating black
STANCHION: 28.6mm steel CP/ED black
LOWER LEGS: Aluminum 9mm open drop out/100mm
FEATURES: Hydraulic lock out
Mechanical lock out
Spring
TRAVEL(mm): 60/100
BRAKE: Disc Only
WEIGHT: 2.355KG

210 series



WHEEL SIZE: 20"
STEERER SIZE: 28.6mm AL7075 alumium
PITCH: 125mm
CROWN: Aluminum coating black
STANCHION: 30 mm AL7075 alumium hard anodize black
LOWER LEGS: Magnesium 9mm open drop out/100mm
FEATURES: Air suspension
Hydraunic lock
TRAVEL(mm): 60
BRAKE: Disc Only
WEIGHT: 1.39KG



212 series



WHEEL SIZE: 20"
STEERER SIZE: 28.6mm Steel
PITCH: 125mm
CROWN: Aluminum coating black
STANCHION: 28.6mm steel CP/ED black
LOWER LEGS: Aluminum 9mm open drop out/100mm
FEATURES: Hydraulic lock out
 Spring
TRAVEL(mm): 60
BRAKE: Disc Only
WEIGHT: 2.24KG

107 series



WHEEL SIZE: 10"
STEERER SIZE: 28.6mm Steel
PITCH: 107mm
CROWN: Aluminum coating black
STANCHION: 25.4mm steel CP/ED black
LOWER LEGS: Aluminum 15mm
 QR/150mm drop out/100mm
FEATURES: (MS) Spring
TRAVEL(mm): 30
BRAKE: Disc Only
WEIGHT: 2.355KG

130 series



WHEEL SIZE: 10"
STEERER SIZE: 28.6mm Steel
PITCH: 130mm
CROWN: Aluminum coating black
STANCHION: 25.4mm steel CP/ED black
LOWER LEGS: Aluminum 9mm open drop out/100mm
FEATURES: (MS) Spring
TRAVEL(mm): 30
BRAKE: Wheel hub brake
WEIGHT: 2.425KG

SP--01

FUNCTION: Hydraulic heigh adjustment seat post
TRAVEL(mm): 100
FEATURES: Remote operated
DIAMETER: ϕ 30.9/ ϕ 31.6mm
WEIGHT: 0.645KG



SP--02

FUNCTION: Hydraulic heigh adjustment seat post
TRAVEL(mm): 120
FEATURES: Remote operated
DIAMETER: ϕ 30.9/ ϕ 31.6mm
WEIGHT: 0.645KG



[illegible]

		Test Report		No.: GZHL2006033021BC	Date: Jun 28, 2020	Page 1 of 2
SHENZHEN LIZHIXIN TECHNOLOGY CO., LTD 5TH FLOOR BUILDING SHANGYUAN ZONE LUNGTANG PARK SHANGCUN VILLAGE GONGMING TOWN GUANGMING DISTRICT						
Sample Description	680 SUSPENSION BICYCLE FRONT FORK					
Style / Item No.	680TA-AIR-RLR-27.5/29"(110)					
Buyer	SHENZHEN LIZHIXIN TECHNOLOGY CO., LTD					
Manufacturer	SHENZHEN LIZHIXIN TECHNOLOGY CO., LTD					
Country of Origin	CHINA					
As above test item and its relevant information regarding to the submission are provided and confirmed by the applicant. SGS is not liable to either the test item or its relevant information, in terms of the accuracy, suitability, reliability or/and integrity accordingly.						
Sample Receiving Date	Jun 17, 2020					
Test Performing Date	Jun 17, 2020 to Jun 28, 2020					
Test Performed	Selected test(s) as requested by applicant					
Test Result(s)	For further details, please refer to the following page(s)					
Signed for and on behalf of SGS-CSTC Standards Technical Services Co., Ltd. Guangzhou Branch						
						
Arthur Mak Authorized Signatory						
						
This report is the property of SGS and is not to be distributed outside the SGS Group without the prior written consent of SGS. This document is subject to the Terms and Conditions of Service printed on the back of this report and is not to be used for any other purpose without the prior written consent of SGS. The SGS Group is not responsible for any loss or damage caused by the use of this report. The SGS Group is not responsible for any loss or damage caused by the use of this report. The SGS Group is not responsible for any loss or damage caused by the use of this report.						
2020年6月28日 15:09:19 地址：广东 广州市天河区黄埔大道西55号 邮编：510640 1 36-85 211880 1 36-85 211890 1 36-85 211910 1 36-85 211920						

SGS

Test Report No.: QZHL2006033022BC Date: Jun 28, 2020 Page 2 of 2

Clauses 4.3.6 of ISO 4210:2015 Cycles - safety requirements for bicycles – Part 2: Requirements for city and trekking, young adult, mountain and racing bicycles

- Bicycle type: Mountain bicycle
- Number of Tested Sample: 1 piece
- Test Result:**

Test Item	Test Requirement / Test Method	Test Result
4.3.6 Front fork — Bending fatigue test plus rearward impact test	When tested by the method described in ISO 4210-4:2015, 5.5, there shall be no fractures in any part of the fork, and the permanent deformation, measured as the displacement of the axis of the wheel axle or simulated axle in relation to the axis of the fork steerer, shall not exceed 45 mm. For composite forks, the running displacement (peak-to-peak value) at the points where the test forces are applied shall not increase by more than 20 % for rigid forks or more than 40 % for suspension forks from the initial values (see ISO 4210-5:2014, 4.6).	Pass

Sample Photo(s):




Sample as received
Sample as received

End of Report


 Singapore Testing Services Pte Ltd
Singapore Branch Office

This report contains information derived solely from the examination conducted under the terms specified hereon. It does not constitute a warranty, nor does it represent an endorsement or approval of products, materials or methods used. The user assumes full responsibility for the application of the results reported herein. Any reproduction or distribution of this report without written permission from SGS is prohibited. All rights reserved. © 2020 SGS. Printed in China.

QZHL AS9922
[www.sgs.com.sg](#)
 Tel: +65 6336 8888 Fax: +65 6336 8889 Email: info@sgs.com.sg

ISO 9001:2015 Certified Company No. 15001
ISO 14001:2015 Certified Company No. 15002
Member of the SGS Group (since 2005)

[illegible][illegible][illegible]

AIR: Air suspension

HLR: Hydraunic lock out and rebound adjustable

RLR: Remote lock out with rebound adjustable

HL: Hydraunic lock out

RL: Remote lock out

RA: Rebound adjustable

ML: Mechanical lock out

AMS: Adjustable

MS: Non adjustable

TA: Through axle

S: Standard stem tube

T: Tapperd stem tube